

VP1220F

System Data	
Continuous Power (IEC 60268-5)	200 W
Peak Power	800 W
Type	2-way full-range loudspeaker
Frequency Response	55 Hz - 20 kHz
Impedance	8 Ohms
Sound Pressure Level (SPL)	93 dB (Full space, 1 W @ 1 m)
Dispersion	70° x 50°
Crossover Frequency	2.5 kHz
Rigging Fittings	ergonomically shaped handle
Components	
HF Driver	1.75" titanium-diaphragm compression driver
LF Driver	12" / 307 mm
Dimensions/Weight	
Width	17.3" / 440 mm
Height	16.9" / 430 mm
Depth	22.6" / 575 mm
Weight	35.7 lbs / 16.2 kg

VP1220

System Data	
Continuous Power (IEC 60268-5)	200 W
Peak Power	800 W
Type	2-way full-range loudspeaker
Frequency Response	50 Hz - 20 kHz
Impedance	8 Ohms
Sound Pressure Level (SPL)	93 dB (Full space, 1 W @ 1 m)
Dispersion	70° x 50°
Crossover Frequency	2.5 kHz
Rigging Fittings	ergonomically shaped handle; integral tripod/stand adapter
Components	
HF Driver	1.75" titanium-diaphragm compression driver
LF Driver	12" / 307 mm
Dimensions/Weight	
Width	14.6" / 370 mm
Height	23.6" / 600 mm
Depth	16.9" / 430 mm
Weight	39.5 lbs / 17.9 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.