

Specifications

Mixer Section	
Inputs	2 x XLR 3 x ¼" TRS balanced 1 x ¼" TS, unbalanced 2 x RCA, unbalanced 1 x 2-channel BEHRINGER ULM Digital Wireless
Outputs	2 x RCA, unbalanced 1 x ¼" TS, unbalanced mono 1 x ¼" TRS, stereo
Wireless Input	
USB dongle (not included)	USB socket accepts signals from max. 2 BEHRINGER ULM microphones
Signal indicator LED	2 (green)
Amplifier	
Maximum output power	2 x 100 W @ 4 Ω*
Frequency response	40 Hz to 25 kHz
Signal-to-noise ratio	85 dB, A-weighted
Outputs	¼" TS, left and right
Speakers	4" woofer and 1" tweeter
Function Switches	
FBQ	Activates the FBQ Feedback Detection System
EQ	Activates the graphic EQ
Graphic EQ	
Type	7-band
Effects	
Type	KLARK TEKNIK
Converter	24-bit Delta-Sigma
Sampling frequency	40 kHz
Display	2-digit, 7-segment
Power Supply / Voltage (Fuses)	
USA / Canada	100-120 V~, 50/60 Hz (T 3.15 A H 250 V)
Japan	100 V~, 50/60 Hz (T 3.15 A H 250 V)
UK / Australia / Europe / Korea / China	220-240 V~, 50/60 Hz (T 3.15 A H 250 V)
Power consumption @ 1/8 rated power	45 W
Mains connection	Standard IEC receptacle
Dimensions / Weight	
Dimensions (H x W x D)	339 x 613 x 186 mm (13.4 x 24.1 x 7.3")
Weight	12 kg (26.5 lbs)

*Independent of limiters and driver protection circuit