

## 6. Specifications

### VS1520

#### System Data

Continuous Power (IEC 60268-5)	150 W
Peak Power	600 W
Type	2-way full-range loudspeaker
Frequency Response	50 Hz – 20 kHz
Impedance	8 Ohms
Sound Pressure Level (SPL)	94 dB (Full space, 1 W @ 1 m)
Dispersion	80° x 40°
Crossover Frequency	3.0 kHz
Rigging Fittings	ergonomically shaped handle; integral tripod/stand adapter

#### Components

HF Driver	Dual electro-dynamic drivers
LF Driver	15" / 385 mm

#### Dimensions/Weight

Width	17.9" / 455 mm
Height	27.0" / 685 mm
Depth	18.3" / 465 mm
Weight	48.3 lbs / 21.9 kg

### VS1220F

#### System Data

Continuous Power (IEC 60268-5)	150 W
Peak Power	600 W
Type	2-way full-range loudspeaker
Frequency Response	55 Hz – 20 kHz
Impedance	8 Ohms
Sound Pressure Level (SPL)	93 dB (Full space, 1 W @ 1 m)
Dispersion	80° x 40°
Crossover Frequency	3.5 kHz
Rigging Fittings	ergonomically shaped handle

#### Components

HF Driver	Dual electro-dynamic drivers
LF Driver	12" / 307 mm

#### Dimensions/Weight

Width	17.3" / 440 mm
Height	16.9" / 430 mm
Depth	22.6" / 575 mm
Weight	34.2 lbs / 15.5 kg